





PRODUCT DESCRIPTION

ax overall height

An undulating shape softly curls along its center to create an organic form constructed of a single panel of transparent acrylic. Further enhancing the form is the captivating effect of the frosted band around the borders and the patterned etching on the acrylic that captures the light. A coordinating wall sconce that features the same curled acrylic material and extends only 4 inches from the wall for ADA compliant applications.

MEASUREMENTS

DIMENSION : 59" L x 9.75" W x 8.5" H

MAX OAH : 120" OAH

CANOPY : 4.754" W x 1.5" H x 23.5" L

HANGING WEIGHT : 8 lb

LAMPING

INPUT VOLTAGE : 120-277V

LUMENS : 4,480 Rated (2,770 Del.)

BULB : 1 x 56W LED DC Integrated , 56W Total

BULB INCLUDED : (Integrated)

DIMMABLE : 3-in-1 Triac, ELV, or 0-10V

CRI : 90 CRI COLOR_TEMP : 3000K

FINISHES OPTION

Black (BK) Gold (GLD)

Polished Chrome (PC)

GLASS

Clear Ribbed 144

MATERIAL

Aluminum, Steel, Acrylic

RATINGS

cETLus Dry Location



ADDITIONAL

RATED LIFE 30000 Hours **OPERATING TEMPERATURE:** -20°C (-4°F), 40°C (104°F)

Always consult a qualified electrician before installing any lighting product.



WESTERN DISTRIBUTION CENTER (HEADQUARTER) 253 NORTH VINELAND AVE I CITY OF INDUSTRY, CA 91746

EASTERN DISTRIBUTION CENTER 101 GARDNER PARK | PEACHTREE CITY, GA 30269