



PRODUCT DESCRIPTION


Elongated tubes of LED light are housed in incredibly small 1" diameter aluminum and suspended by nearly invisible support cables. Engineered to connect the various lengths end-to-end or with use of the rigid, angled adapters, adds endless applications for creativity and function. Each length includes a power feed within a surface mounted canopy and non-electrical support cables that standoff using ceiling anchors. The continuous run pendants in this series are a welcome convenience for commercial applications. Lengths range from 36" to impressive 96" long. Individually, the fixtures provide ample lighting downward with minimal disruption to the architectural sight lines of a space. Available in Black, White, and brushed Aluminum finishes these are exemplary streamlined forms with functional purpose.

MEASUREMENTS

- DIMENSION : 47" L x 1.5" W x 1.25" H
- MAX OAH : 121" OAH
- CANOPY : 5" W x 1" H x 5" L
- HANGING WEIGHT : 3.53 lb




LAMPING

- INPUT VOLTAGE : 120-277V
- LUMENS : 2,650 Rated (2,100 Del.)
- BULB : 1 x 34W LED PCB Integrated , 34W Total
- BULB INCLUDED : (Integrated)
- DIMMABLE : Universal 3-in-1
- CRI : 90 CRI
- COLOR_TEMP : Select 30/35/40K



*max overall height

FINISHES OPTION

-  Black (BK)
-  Satin Aluminum (SA)
-  White (WT)

GLASS

Frosted 90

MATERIAL

Acrylic, Aluminum

RATINGS

cETLus
Dry Location



ADDITIONAL

RATED LIFE 50000 Hours
OPERATING TEMPERATURE:
-20°C (-4°F), 40°C (104°F)

Always consult a qualified electrician before installing any lighting product.



WESTERN DISTRIBUTION CENTER (HEADQUARTER)
253 NORTH VINELAND AVE | CITY OF INDUSTRY, CA 91746
EASTERN DISTRIBUTION CENTER
101 GARDNER PARK | PEACHTREE CITY, GA 30269
P. 626.956.4200 | F. 626.956.4225 | maxlighting.com